



EBM with collet

EBM with drill chuck

## Technical data

Type with collet		EBM 19000 S	EBM 5200 S	EBM 2900 S	EBM 2400 S	EBM 1200 S
Order-No.		60001-04-7	29937-63-7	29937-61-7	29937-62-7	60003-85-7
Type with drill chuck		—	EBM 38-5200 B	EBM 38-2900 B	EBM 38-2400 B	EBM 38-1200 B
Order-No.			29937-64-7	60009-26-7	60009-25-7	60008-71-7
Free speed	rpm	19 000	5 200	2 900	2 400	1 200
Motor power	Watt	380	380	380	380	380
Drill chuck clamping range	mm	—	1–10	1–10	1–10	1–10
Direction of rotation *		clockwise	clockwise	clockwise	clockwise	clockwise
ER collet included	mm	6	6	6	6	6
ER collets available	mm   "	3   5   8   10	3   5   8   10	3   5   8   10	3   5   8   10	3   5   8   10
Exhaust air **		to the rear	to the rear	to the rear	to the rear	to the rear
Noise level	dB(A)	72	72	72	72	72
Air consumption	l / sec	8.5	8.5	8.5	8.5	8.5
Weight with collet   drill chuck	kg	1.12   1.20	1.12   1.20	1.12   1.20	1.12   1.20	1.12   1.20
Connection air supply (hose)	∅ mm, inside / outside	10   12	10   12	10   12	10   12	10   12

Power and free speed at 6 bar operating pressure. Compressed air quality: lubricated (2–3 drops per minute).

\* Direction of rotation: *counterclockwise* on request | \*\* Exhaust air: with *guided exhaust air* upon request

The suitable accessories: [page 29](#).

