

350° 300° INT EXT



Description

- Potence sur fût suspendue articulée type PFSAM pour service intérieur, à rotation 350° pour le bras 1 et 300° pour le bras 2.
- Ce type de potence ne peut être motorisé.
- Flèche théorique sous charge nominale = environ 1/250^e de la portée + hauteur sans dépasser 1/100^e de la portée seule.
- Protection : système 3 couches.
- Finition polyuréthane jaune RAL 1028.
- Vitesse de levage maximum = 16 m/min.
- Emballage sous film rétractable pour transport par camion, non compatible transport maritime.

CMU Max capacity	Portée Span
Kg	m
50	2
50	3
50	4
50	5
80	2
80	3
80	4
80	5

CMU Max capacity	Portée Span
Kg	m
125	2
125	3
125	4
125	5
250	2
250	3
250	4

CMU Max capacity	Portée Span
Kg	m
500	2
500	3
1000	2

Description

- Articulated pillar jib crane suspended for indoor use, 350° rotation for arm 1 and 300° rotation for arm 2.
- This type of jib crane cannot be motorized.
- Theoretical deflection under nominal load = approximately 1/250th of the span + height, without exceeding 1/100th of the span in itself.
- Protection: 3-layer system.
- RAL 1028 yellow polyurethane finish.
- Maximum hoisting speed = 16 m/min.
- Packing under shrink film planned for transport by truck. Not suitable for sea freight.

Prix départ usine, emballage compris. | Ex-works prices, packaging included.

OPTIONS

Accessoires de levage | Lifting accessories

Palan manuel
Manual hoist
Palan électrique autre que PACK PROMO
Electric hoist other than PACK PROMO

Électrique | Electrical

Interrupteur cadenassable
Lockable main switch
Câble sous tube
Cable in tube

Fixations | Attachment kit

Semelle à cheviller
Base plate for chemical anchors

Accessoires de levage | Lifting accessories

Anneau d'amarrage palan
Rigging ring
Peinture intérieure RAL spécifique
Specific RAL finish for indoor use
Peinture 4 couches polyuréthane sur apprêt epoxy RAL 1028
Polyurethan painting RAL 1028 on epoxy primer for outdoor use
Peinture 4 couches polyuréthane sur apprêt epoxy RAL spécifique
Polyurethan painting with specific color on epoxy primer for outdoor use
Galvanisation à chaud
Hot dip galvanizing
Abri interrupteur cadenassable
Cover for the lockable switch
Capotage pour palan
Covering for hoist

Documentation | Documentation

Note de calcul (prix net)
Calculation note (net price)